

you can
Canon

Black & White printers for
medium-sized workgroups

iR1018/1022 Series

iR1018J, iR1018, iR1022A

iR1022F, iR1022i, iR1022iF

iR2018/2030 Series

iR2018/i, iR2022/i

iR2025/i, iR2030/i

PRINT
SCAN
COPY
SEND



Business never looked better in black & white

Big impact, small size. Now you can ensure your business communications create a big impression – with only a little effort. Both the Canon iR1018/1022 and iR2018/2030 Series combine the skills of many devices into small space-saving multifunctional units, giving you high quality printing, scanning, copying and sending.

COPY SCAN PRINT SEND

BEST OF BREED ALL-IN-ONE DEVICES, WITH THE SERVICE AND SUPPORT TO MATCH

By connecting these intelligent all-in-one devices to your network, you can add powerful communication tools to your business. From entry-level everyday black & white printers to more sophisticated document and publishing capabilities up to A3, you'll find what you're looking for with these two great ranges.

You'll also enjoy expert installation, training and on-site service, plus pre-determined Service Level Agreements – and with click charging, you only pay for what

CANON EASY SERVICE PLAN

If you prefer to buy from an authorised Canon partner, you can still benefit from Canon's quality service with our Easy Service Plan. Any Canon device you buy is maintained by us and our authorised partners, so you don't have to worry about a thing.

• **Value and cost control**

A fixed maintenance fee for the duration of your Easy Service Plan contract.

• **Product knowledge and service**

All Canon Authorised engineers have full knowledge of

• **On-site maintenance and system support**

An engineer will be on their way to you within 24 hours of you placing a call.

• **Help as and when you need it**

We're only ever a call or email away, via our Call Centre and Canon Helpdesk.



Canon iR1018/1022 – Communicate with incredible speed

Entry level pricing, high quality printing

Sitting comfortably on your desk, Canon iR1018/22 printers will help you print, copy and fax desktop communications quickly in black and white, plus you can scan and send in glorious colour



**FAST, EFFECTIVE,
PRODUCTIVE** Canon iR1018/22
printers meet
the specific requirements of small
business or workgroups needing
compact, cost-effective power.
You can print 18-22 pages per
minute and also scan and send
information directly from the

**SAVE SPACE, AND
THE ENVIRONMENT TOO**

A compact footprint means you
don't have to use valuable floor
space for different devices, you
get everything you need in one
small desktop model. As part of
Canon's commitment to reducing
environmental impact, these models
automatically go into
energy-saving sleep mode when the
device is not in use – and can power
back up in seconds as soon as they
are needed.

COPY SCAN PRINT SEND



C-EXV18 Toner

Business has never looked better in black & white – especially with our genuine toner.



iR1018J

- Copy at up to 18 ppm
- Sits comfortably on your



iR1022A

- Print/copy at up to 22ppm
- Automatic Document Feeder (ADF)



iR1022F

- Print/copy/fax at up to 22ppm
- Automatic Document Feeder (ADF)
- Built-in modem for speedy faxing
- Store up to 200 fax numbers

		COPY	PRINT	ADF	FAX	SCAN	SEND
iR1018J	18ppm	●					
iR1018	18ppm	●	●			●	
iR1022A	22ppm	●	●	●		●	
iR1022F	22ppm	●	●	●	●	●	
iR1022i	22ppm	●	●	●		●	●
iR1022iF	22ppm	●	●	●	●	●	●

● STANDA



iR1022i

- Print/copy/scan/send at up to 22ppm
- Automatic Document Feeder (ADF)
- Scan colour documents
- Email scanned documents directly to recipient



iR1022iF

- Print/copy/scan/fax/send at up to 22ppm
- Automatic Document Feeder (ADF)
- Scan colour documents
- Email scanned documents directly to recipient

COPY SCAN PRINT SEND



C-EXV14 Toner

Business has never looked better in black & white – especially with our genuine toner.



iR 2016J

- Copy at up to 16ppm
- Energy Saving mode & fast recovery



iR 2018/i NEW

- Print/copy/fax/send at up to 18ppm
- Print up to A3



iR 2022/i NEW

- Remote fleet control with iWMC and RUI
- Additional finishing and paper capacity options

		COPY	PRINT	ADF	FAX	SCAN	SEND
iR 2016J	16ppm	●		○			
iR 2018	18ppm	●	●	○	○	○	
iR 2018i	18ppm	●	●	●	○	○	●
iR 2022	22ppm	●	●	○	○	○	
iR 2022i	22ppm	●	●	●	○	○	●
iR 2025	25ppm	●	●	○	○	○	○
iR 2025i	25ppm	●	●	●	○	○	●
iR 2030	30ppm	●	●	○	○	○	○
iR 2030i	30ppm	●	●	●	○	○	●

● STANDARD ○



iR 2025/i NEW

- Print/copy/fax/send at up to 25ppm
- Remote fleet control with iWMC and RUI
- Additional finishing and paper capacity options
- Easy-to-use interface



iR 2030/i NEW

- Print/copy/fax/send at up to 30ppm
- Additional finishing and paper capacity options*
- Remote fleet control with iWMC and RUI*
- Easy-to-use interface and touch-screen
- Integration into uniFLOW*
- Optional Card Reader for secure access control*

COPY SCAN PRINT SEND

Canon iR2018/2030 – Get your message across in style

Add a little sophistication to your black & white documents

The Canon iR2018/30 series has been created to deliver fantastic value printing, scanning and copying for up to A3, and publishing capabilities if you require them. All of which enables you to manage cost, productivity, quality of output and your impact on the environment.



SIMPLE, PROFESSIONAL, VERSATILE

Create high quality professional-looking black & white documents with ease, at up to 1,200 dpi (with URFII lite), with simple finishing options such as double-

EASY ADMINISTRATION WITH CENTRAL MANAGEMENT

All devices in this range can be easily connected to your IT network, enabling you to take advantage of intelligent software solutions. For example, iW Management Console (iWMC), helps you manage, monitor and control multiple networked devices from a single point of control. Plus, Remote User Interface (RUI), gives users easy access and management of any print device connected to your network, direct

COPY SCAN PRINT SEND

Specifications iR1018/iR1022 Series

Type	Desktop
Maximum Original Size	A4
Copy Sizes	Cassette: A4, Stack Bypass: A5 – A4, Envelopes
Resolution	Copying: 600dpi x 600dpi, 1200dpi equivalent x 600dpi Printing: 1200dpi equivalent x 600dpi (PCL, UFR II LT) 256
Gradations Copy/Print Speed (iR1022A/22F/22i/22iF)	A4: 18cpm (iR1018J/1018), 22cpm
Magnification	Zoom: 50-200%, Fixed: 50%, 70%, 100%, 141%, 200%
First copy time	8.0 sec or less (iR1018J/1018), 12.0 sec or less (iR1022A/22F/22i/22iF)
Warm-Up Time	Less than 13.5 sec. for iR1018J/18/22A/22F less than 16 sec. for iR1022i/22iF
Multiple Copies/Prints	1 to 99 sheets
Double-Sided	Automatic stackless
Paper weight	Cassette: 64 to 90g/m ² , Stack Bypass: 56 to 128g/m ² Double-Sided: 64 to 80g/m ²
Cassette	A4
Paper Capacity (80g/m ²)	500 sheets x 1 cassette, Stack Bypass: 100 sheets
Standard	500 sheets x 1 cassette, Max. Total paper capacity: 1,100 sheets
Optional	Canon Custom Processor, 192MHz
CPU	64MB (iR1018J), 128MB (iR1018/22A/22F), 256MB (iR1022i/22iF)
Memory	iR1018J USB2.0
Interface	iR1018/22A/22F Ethernet (100Base-TX/10Base-T) optional, USB2.0 iR1022i/iF Ethernet (100Base-TX/10Base-T), USB2.0
Power Supply	220V AC to 240V AC ±10% (50/60Hz)
Power Consumption(W)	954W max.
Dimensions (WxDxH)	520 x 457 x 378 mm (iR1018J/18) 520 x 457 x 453 mm (iR1022A/22F/22i/22iF)
Weight	Approx. 22.0kg (iR1018J/18) Approx. 24.1kg (iR1022A/22F/22i/22iF)
SEND FUNCTION ¹	
Scan Speed with DADF	BW: 20ipm A4 300dpi, Colour: 6ipm A4 300dpi
Scan Resolution	BW: 200x100dpi, 200dpi, 200x400dpi, 300dpi, 400dpi, 600dpi Colour: 100dpi, 150dpi, 200dpi, 300dpi (JPEG) 300dpi (High compression PDF)
Destinations	E-Mail/Internet FAX (SMTP), PC (SMB,FTP), iWDM Gateway
Address book	Local (Max.200)
File Format	Single: (BW) TIFF, PDF – (Colour) JPEG, High compression PDF

PRINTER FUNCTION	
PDL	UFR II LT (Standard for iR1018/22A/22F/22i/22iF), PCL 5e/6 (Standard for iR1022i/22iF)
Resolution	1200dpi equivalent x 600dpi (PCL, UFR II LT), 1200dpi x 1200dpi (UFR II LT with PCL option)
Memory	128MB (iR1018/22A/22F), 256MB (iR1022i/22iF)
CPU	Canon Custom Processor, 192MHz (Uses Main Unit CPU)
PCL Fonts	Roman113 (including Barcode Fonts)
Supported OS	PCL: Windows 98/Me/2000/XP/2003 Server UFR II LT: Windows 98/Me/2000/XP/2003 Server, Mac OS 10.2.8-10.4.3
Interface (Standard)	iR1018/22A/22F Ethernet (100Base-TX/10Base-T) optional, USB2.0 iR1022i/iF Ethernet (100Base-TX/10Base-T), USB2.0
Network Protocol	TCP/IP (LPD/RAW/ Port 9100)
DADF ²	
Paper size	A4R, A5R, A5
Paper weight	50 g/m ² to 105 g/m ²
Max. Number of originals	A5R to A4: 50 sheets (80 g/m ²)
Document Scanning speed (max.)	
Copy Scan	iR1022A/1022F/1022i/1022iF: A4 20 ipm BW: 20ipm A4 300dpi, Colour: 6ipm A4 300dpi
OTHER ACCESSORIES	iR1018/22 Plain Pedestal, Cassette Feeding Unit, Cassette, Card Reader-E1, Card Reader Attachment, Network Kit (Standard for iR1022i/22iF), PCL Kit (Standard for iR1022i/22iF)

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. TM and [®]: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon Recommends you use Canon Media for the best results. Please check media(paper) compatibility list to see which variety of paper/media is recommended. Environmentally considerate production methods ensure that Canon complies with the European WEEE** directives. Lead and hazardous substances are prohibited from the manufacturing process. In addition the machine conforms to the International Energy Star Program.

1 Standard for iR1022i/22iF only
2 Standard for iR1022A/22F/22i/22iF

Specifications iR2018/2030 Series

Type	Desktop
Maximum Original Size	A3, 297 x 432mm
Copy Sizes	Cassette: A5 – A3, Stack Bypass: A5R-A3, Envelopes
Resolution	Copying: 600dpi x 600dpi, 1200dpi equivalent x 600dpi Printing: 1200dpi equivalent x 600dpi(PCL, UFR II LT), 1200dpi x 1200dpi (UFR II LT), 256 Gradations
Copy/Print Speed	A4: 18cpm(iR2018/i), 22cpm(iR2022/i), 25cpm(iR2025/i) 30cpm(iR2030/i), A3: 15cpm for iR2018/18i/22/22i/25/30/i
Magnification	Zoom: 50-200%, Fixed: 50%, 70%, 100%, 141%, 200%
First copy time	6.9 sec
Warm-Up Time	Approx. 26 seconds (Approx 14 seconds for iR2018/22)
Multiple Copies/Prints	1 to 99 sheets
Double-Sided	Optional Automatic stackless (Standard for iR2025/30/i)
Paper weight	Cassette: 64 to 90g/m ² , Stack Bypass: 64 to 128g/m ² Double-Sided: 64 to 90g/m ²
Cassette	Universal: A5 to A3
Paper Capacity	Standard
Standard	250 sheets x 2 cassettes (80g/m ² , 500 sheets) for iR2022/22i/25/30/i 250 sheets x 1 cassette (80g/m ² , 250 sheets) for iR2018/i
Multi Stack Bypass	80 sheets (80g/m ²) for A5R to A4, 50 sheets for A3 (80g/m ²)
Optional	250 sheets x 2 cassettes (500 sheets) for iR2022/25/30/i 250 sheets x 3 cassettes (750 sheets) for iR2018/i 250 sheets x 1 cassette for iR2018/i
Max. Total paper capacity	1,080 sheets
CPU	Canon Custom Processor, 192MHz
Memory	256MB (128MB for iR2018/22)
Interface	Ethernet (100Base-TX/10Base-T), USB2.0
Power Supply	220V AC to 240V AC ±10% (50/60Hz)
Power Consumption(W)	1.5KW max.
Dimensions (WxDxH)	622 x 638 x 665.4mm (iR2022), 622 x 676 x 757 mm (iR2022i/25i/30i), 622 x 638 x 665.4 mm (iR2025/30)
Weight	622 x 638 x 580.4mm (iR2018), 622 x 676 x 672 mm (iR2018i) Approx. 53.0 kg (iR2022i/25i/30i), Approx. 47.0 kg (iR2025/30) Approx. 47.0 kg (iR2018i), Approx. 41.0 kg (iR2018)
SEND FUNCTION ¹	
Scan Speed with DADF	BW: 20ipm A4 300dpi, Colour: 6ipm A4 300dpi
Scan Resolution	BW: 100dpi, 150dpi, 200x100dpi, 200dpi, 200x400dpi, 300dpi, 400dpi, 600dpi, Colour: 100dpi, 150dpi, 200dpi, 300dpi
Destinations	E-Mail/Internet FAX (SMTP), PC (SMB,FTP), iWDM Gateway
Address book	Local (Max.500)
File Format	Single: JPEG, TIFF, PDF / Multi: TIFF, PDF
Pull Scan	Network TWAIN driver (75-300dpi) (standard for all models)
PRINTER FUNCTION ²	
PDL	UFR II LT, PCL 5e, PCL
6 Resolution	1200dpi equivalent x 600dpi(PCL, UFR II LT), 1200dpi x 1200dpi(UFR II LT)
Memory	(PCL Kit-V1 required for iR2018/22 and PCL Kit-W1 required for iR2025/30) 256MB (iR2018/22 – 128MB standard, 256MB optional with PCL Kit-V1 (Uses Main unit RAM))
CPU	Canon Custom Processor 192MHz (Uses Main unit CPU)
PCL Fonts	Roman113 (including Barcode Fonts) (For iR2018/22 only available with PCL Kit-V1)
Supported OS	PCL: Windows 98/Me/2000/XP/2003 Server/Vista, UFR II LT: Windows 98/Me/2000/XP/2003 Server/Vista, Mac OS X 10.2.8 or later
Interface(Standard)	Ethernet(100Base-TX/10Base-T), USB 2.0

DADF-P2 ³	
Paper size	A3-A5R
Paper weight	52 g/m ² to 105 g/m ²
Max. Number of originals	A5R to A4: 50sheets (80 g/m ²) A3: 25sheets (80 g/m ²)
Document Scanning speed (max.)	
Copy Scan	A4 20 ipm
Dimensions (WxDxH)	BW: 20ipm A4 300dpi, Colour: 6ipm A4 300dpi
Weight	565 x 489.4 x 122 mm Approx. 7.0kg
CASSETTE FEEDING MODULE-PI/Q1	
Type	Front-loading adjustable drawers
Paper Weight	64 to 90g/m ²
Paper Capacity	P1: 250 sheets (80 g/m ²) x 1 cassettes for iR2018/i Q1: 250 sheets (80 g/m ²) x 2 cassettes for iR2022/25/30/i
Dimensions(W x D x H)	P1 and Q1: 250 sheets (80 g/m ²) x 3 cassettes for iR2018/i
Weight	P1: 580.3 x 569.3 X 116.8 mm Q1: 580.3 x 569.3 X 201.8 mm P1: Approx. 6.0kg, Q1: Approx. 12.0kg
FINISHER-U2	
Number of trays	One stack tray + Optional Tray (Inner)
Tray capacity	Standard: A4/A5/A5R :770 sheets or 100mm A4R/A3: 380 sheets or 50mm
With Optional Tray	TrayA: A4/A5/A5R 200 sheets, A4R/A3: 150 sheets TrayB: A4/A5/A5R 200 sheets, A4R/A3: 150 sheets
Staple position	Corner
Staple capacity	A4: 50 sheets, A3/A4R: 30 sheets
Weight	Approx. 10.0kg
INNER 2 WAY TRAY-E2	
Tray capacity	TrayA: A4 100 sheets, Other 50 sheets, TrayB: A4 250 sheets
Weight	Other 100 sheets Approx. 1.5kg
OTHER ACCESSORIES	PCL Printer Kit-W1, Fax Panel-B1 (Optional for iR2018/22, standard on other models), Barcode Printing Kit-B1, Colour Send Kit-L1 (Not for iR2018/22), Super G3 FAX Board-AA1, Duplex Unit-B1, iR2016/20 Plain Pedestal High (for 2cassettes configuration), iR2016/20 Plain Pedestal Low (for 4cassettes configuration), FL Cassette-AC1, PLATEN COVER Type J, Staple Cartridge-J1, Stamp Ink Cartridge-C1, Additional Finisher Tray-C1 (Optional for Finisher-U2), Card Reader-E1, Card Reader Attachment-D1, Power Supply Kit-Q1(Required for Finisher-U2 and Cassette Feeding Module-Q1), Signal Converter For NEXUS

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. TM and [®]: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon Recommends you use Canon Media for the best results. Please check media(paper) compatibility list to see which variety of paper/media is recommended. Environmentally considerate production methods ensure that Canon complies with the European WEEE** directives. Lead and hazardous substances are prohibited from the manufacturing process. In addition the machine conforms to the International Energy Star Program.

you can
Canon

Canon Inc.
www.canon.com

Adres

Canon Europa N.V.
www.canon-europe.com

English Edition
© Canon Europa N.V., 2007 (0907)



Canon's GENUINE logo means quality all-round